

Antcom's **G3 Antenna**, Active **L1 Glonass + L1 GPS + OmniStar** Antenna, P/N: **G3Ant-2AMNS1** **Magnetic Mount Configuration** **(with Filters, better RTK Performance, Optimized for L1 Glonass & L1 GPS & OmniStar)**

		7		6		5		4		3		1																																																																																	
<p>NOTICE OF PROPRIETARY RIGHTS THIS DOCUMENT CONTAINS CONFIDENTIAL, TRADE SECRET, AND/OR PROPRIETARY INFORMATION. ANY DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONDITIONED UPON YOUR ACCEPTANCE OF THIS USE IS LIMITED TO THE USE OF THE INFORMATION ONLY AND DOES NOT INCLUDE REPRODUCTION OR TRANSMISSION IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.</p>		SPECIFICATIONS										<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2"></th> <th colspan="2">REVISIONS</th> </tr> <tr> <th>ZONE</th> <th>REV</th> <th>DESCRIPTION</th> <th>DATE</th> <th>APPROVED</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>				REVISIONS		ZONE	REV	DESCRIPTION	DATE	APPROVED																																																																							
				REVISIONS																																																																																									
ZONE	REV	DESCRIPTION	DATE	APPROVED																																																																																									
				<p>ELECTRICAL:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>OmniSTAR / L-Band L6 Galileo B1 Compass</th> <th>L1 GPS E1, E2 Galileo L1 IRNSS</th> <th>L1 GLONASS</th> </tr> </thead> <tbody> <tr> <td>FREQUENCY:</td> <td>1542.50 ± 14.0 MHz 1542.50 ± 5.0 MHz 1561.098 ± 10.0 MHz</td> <td>1575.42 ± 15.0 MHz 1575.42 ± 17.0 MHz 1575.42 ± 12.0 MHz</td> <td>1609 ± 7.0 MHz</td> </tr> <tr> <td>RADIATION PATTERN:</td> <td colspan="3" style="text-align: center;">HEMISPHERICAL</td> </tr> <tr> <td>POLARIZATION:</td> <td>RHCP</td> <td>RHCP</td> <td>RHCP</td> </tr> <tr> <td>VSWR:</td> <td>< 2.0:1</td> <td>< 2.0:1</td> <td>< 2.0:1</td> </tr> <tr> <td>IMPEDANCE:</td> <td>50 ohms</td> <td>50 ohms</td> <td>50 ohms</td> </tr> <tr> <td>ANTENNA GAIN (dBd):</td> <td>Free Space</td> <td>5m G.P</td> <td>Free Space</td> </tr> <tr> <td>@ 90° Elevation:</td> <td>+1.9</td> <td>+1.0</td> <td>+4.1</td> </tr> <tr> <td>@ 10° Elevation:</td> <td>-3.0</td> <td>-5.7</td> <td>-2.8</td> </tr> <tr> <td>@ 20° Elevation:</td> <td>-3.9</td> <td>-3.9</td> <td>-1.9</td> </tr> <tr> <td>@ 30° Elevation:</td> <td>-2.6</td> <td>-3.0</td> <td>-0.4</td> </tr> <tr> <td>@ 60 - 90° Elevation:</td> <td>> +0.8</td> <td>> +0.2</td> <td>> 2.9</td> </tr> <tr> <td>BEAM WIDTH (3dB):</td> <td>95 Deg.</td> <td>97 Deg.</td> <td>95 Deg.</td> </tr> <tr> <td>AXIAL RATIO:</td> <td>1 dB</td> <td>1 dB</td> <td>1 dB</td> </tr> <tr> <td>LIGHTNING PROTECTION:</td> <td colspan="3" style="text-align: center;">DC GROUNDING</td> </tr> <tr> <td>LNA GAIN:</td> <td>33 dB</td> <td>32 dB</td> <td>31 dB</td> </tr> <tr> <td>LNA NOISE FIGURE:</td> <td>3.0 dB</td> <td>3.0 dB</td> <td>3.0 dB</td> </tr> <tr> <td>LNA P1dB Out:</td> <td>+13 dBm</td> <td>+13 dBm</td> <td>+13 dBm</td> </tr> <tr> <td>LNA DC POWER:</td> <td colspan="3" style="text-align: center;">2.5V/20mA, 3V/29mA, 3.3V/35mA, (2.5-24)V/≤50mA</td> </tr> <tr> <td>POWER HANDLING:</td> <td colspan="3" style="text-align: center;">1 Watt CW, Optional: 10 Watts 1 Microsec Pulse (-AL-)</td> </tr> </tbody> </table>									OmniSTAR / L-Band L6 Galileo B1 Compass	L1 GPS E1, E2 Galileo L1 IRNSS	L1 GLONASS	FREQUENCY:	1542.50 ± 14.0 MHz 1542.50 ± 5.0 MHz 1561.098 ± 10.0 MHz	1575.42 ± 15.0 MHz 1575.42 ± 17.0 MHz 1575.42 ± 12.0 MHz	1609 ± 7.0 MHz	RADIATION PATTERN:	HEMISPHERICAL			POLARIZATION:	RHCP	RHCP	RHCP	VSWR:	< 2.0:1	< 2.0:1	< 2.0:1	IMPEDANCE:	50 ohms	50 ohms	50 ohms	ANTENNA GAIN (dBd):	Free Space	5m G.P	Free Space	@ 90° Elevation:	+1.9	+1.0	+4.1	@ 10° Elevation:	-3.0	-5.7	-2.8	@ 20° Elevation:	-3.9	-3.9	-1.9	@ 30° Elevation:	-2.6	-3.0	-0.4	@ 60 - 90° Elevation:	> +0.8	> +0.2	> 2.9	BEAM WIDTH (3dB):	95 Deg.	97 Deg.	95 Deg.	AXIAL RATIO:	1 dB	1 dB	1 dB	LIGHTNING PROTECTION:	DC GROUNDING			LNA GAIN:	33 dB	32 dB	31 dB	LNA NOISE FIGURE:	3.0 dB	3.0 dB	3.0 dB	LNA P1dB Out:	+13 dBm	+13 dBm	+13 dBm	LNA DC POWER:	2.5V/20mA, 3V/29mA, 3.3V/35mA, (2.5-24)V/≤50mA			POWER HANDLING:	1 Watt CW, Optional: 10 Watts 1 Microsec Pulse (-AL-)			<p>MECHANICAL:</p> <p>SIZE: DIAMETER: 2.71 in. [68.81 mm] HEIGHT: 0.864 in. [21.96 mm]</p> <p>WEIGHT: 5.7 oz. (162 g)</p> <p>FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL BASE IRIDITE PER MIL-C-5541F Class 1A</p> <p>MATERIAL: 6061-T6 ALUMINUM ALLOY BASE COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT, SKYDROL RESISTANCE, AND FIRE RETARDANT</p> <p>CONNECTOR: SMA FEMALE CONNECTOR</p>	
					OmniSTAR / L-Band L6 Galileo B1 Compass	L1 GPS E1, E2 Galileo L1 IRNSS	L1 GLONASS																																																																																						
FREQUENCY:	1542.50 ± 14.0 MHz 1542.50 ± 5.0 MHz 1561.098 ± 10.0 MHz	1575.42 ± 15.0 MHz 1575.42 ± 17.0 MHz 1575.42 ± 12.0 MHz	1609 ± 7.0 MHz																																																																																										
RADIATION PATTERN:	HEMISPHERICAL																																																																																												
POLARIZATION:	RHCP	RHCP	RHCP																																																																																										
VSWR:	< 2.0:1	< 2.0:1	< 2.0:1																																																																																										
IMPEDANCE:	50 ohms	50 ohms	50 ohms																																																																																										
ANTENNA GAIN (dBd):	Free Space	5m G.P	Free Space																																																																																										
@ 90° Elevation:	+1.9	+1.0	+4.1																																																																																										
@ 10° Elevation:	-3.0	-5.7	-2.8																																																																																										
@ 20° Elevation:	-3.9	-3.9	-1.9																																																																																										
@ 30° Elevation:	-2.6	-3.0	-0.4																																																																																										
@ 60 - 90° Elevation:	> +0.8	> +0.2	> 2.9																																																																																										
BEAM WIDTH (3dB):	95 Deg.	97 Deg.	95 Deg.																																																																																										
AXIAL RATIO:	1 dB	1 dB	1 dB																																																																																										
LIGHTNING PROTECTION:	DC GROUNDING																																																																																												
LNA GAIN:	33 dB	32 dB	31 dB																																																																																										
LNA NOISE FIGURE:	3.0 dB	3.0 dB	3.0 dB																																																																																										
LNA P1dB Out:	+13 dBm	+13 dBm	+13 dBm																																																																																										
LNA DC POWER:	2.5V/20mA, 3V/29mA, 3.3V/35mA, (2.5-24)V/≤50mA																																																																																												
POWER HANDLING:	1 Watt CW, Optional: 10 Watts 1 Microsec Pulse (-AL-)																																																																																												
				<p>ENVIRONMENTAL:</p> <p>TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C] 70,000 ft. 30 G's HERMETICALLY SEAL</p> <p>FEDERAL & MILITARY SPECIFICATIONS: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455</p> <p>ACCEPTANCE TEST PROCEDURE: ATP-GPS-L1L2-100</p>																																																																																									
								<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>QUANTITY REQD</th> <th>DESCRIPTION</th> <th>PARTS LIST</th> <th>PART NO</th> <th>FINISH</th> <th>ITEM NO</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>ADHESIVE GASKET</td> <td>Magnet-Cover-2</td> <td>-</td> <td>-</td> <td>5</td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>4</td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>3</td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>2</td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>1</td> </tr> </tbody> </table>								QUANTITY REQD	DESCRIPTION	PARTS LIST	PART NO	FINISH	ITEM NO	1	ADHESIVE GASKET	Magnet-Cover-2	-	-	5	1					4	1					3	1					2	1					1																																										
QUANTITY REQD	DESCRIPTION	PARTS LIST	PART NO					FINISH	ITEM NO																																																																																				
1	ADHESIVE GASKET	Magnet-Cover-2	-	-	5																																																																																								
1					4																																																																																								
1					3																																																																																								
1					2																																																																																								
1					1																																																																																								
<p style="font-size: 24pt; color: purple; text-align: center;">P/N: G3Ant-2AMNS1 Connector Color</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>SIZE:</th> <th>LNA:</th> <th>CABLE'S LENGTH:</th> <th>CONNECTOR:</th> <th>COLOR:</th> </tr> </thead> <tbody> <tr> <td>1: 2" SQ.</td> <td>42: ARINC 743</td> <td>A: WITH LNA</td> <td>S: SMA:</td> <td>-1: GLOSS WHITE #17925 PER FED-STD-595B</td> </tr> <tr> <td>1.9: 1.9" SQ.</td> <td>52: 2.6" DIA. ON 5" GROUND PL. AINE</td> <td>X: NO CABLE</td> <td>M: MCX; MM: MMCX</td> <td>-2: LUSTERLESS GRAY #36320 PER FED-STD-595B</td> </tr> <tr> <td>2: 2.6" DIA.</td> <td>72: 7" DIA. CHOKER RING</td> <td></td> <td>T: THC; N: N</td> <td>-3: OLIVE DRAB GREEN #34084 PER FED-STD-595B</td> </tr> <tr> <td>3: 3.5" DIA.</td> <td></td> <td></td> <td></td> <td>-4: LUSTERLESS BLACK #37038 PER FED-STD-595B</td> </tr> <tr> <td>4: MINI ARINC</td> <td></td> <td></td> <td></td> <td>-5: TAN #F: #S 23446 or 33446, FED-STD-595</td> </tr> </tbody> </table>		SIZE:	LNA:	CABLE'S LENGTH:	CONNECTOR:	COLOR:	1: 2" SQ.	42: ARINC 743	A: WITH LNA	S: SMA:	-1: GLOSS WHITE #17925 PER FED-STD-595B	1.9: 1.9" SQ.	52: 2.6" DIA. ON 5" GROUND PL. AINE	X: NO CABLE	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B	2: 2.6" DIA.	72: 7" DIA. CHOKER RING		T: THC; N: N	-3: OLIVE DRAB GREEN #34084 PER FED-STD-595B	3: 3.5" DIA.				-4: LUSTERLESS BLACK #37038 PER FED-STD-595B	4: MINI ARINC				-5: TAN #F: #S 23446 or 33446, FED-STD-595	<p style="text-align: center;">ANTCOM CORP. TORRANCE CALIFORNIA</p> <p style="text-align: center;">2.6in Dia. FLUSH MAG MOUNT L1 Glonass + L1 GPS + OmniStar G3 ANTENNA</p> <p style="text-align: center;">D3CVE1 G3Ant-2AMNS1</p> <p style="text-align: center;">SCALE: 1/1 SHEET 1 OF 1</p>																																																													
		SIZE:	LNA:	CABLE'S LENGTH:	CONNECTOR:	COLOR:																																																																																							
1: 2" SQ.	42: ARINC 743	A: WITH LNA	S: SMA:	-1: GLOSS WHITE #17925 PER FED-STD-595B																																																																																									
1.9: 1.9" SQ.	52: 2.6" DIA. ON 5" GROUND PL. AINE	X: NO CABLE	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B																																																																																									
2: 2.6" DIA.	72: 7" DIA. CHOKER RING		T: THC; N: N	-3: OLIVE DRAB GREEN #34084 PER FED-STD-595B																																																																																									
3: 3.5" DIA.				-4: LUSTERLESS BLACK #37038 PER FED-STD-595B																																																																																									
4: MINI ARINC				-5: TAN #F: #S 23446 or 33446, FED-STD-595																																																																																									
<p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRACTIONS DECIMAL ANGLES ± 1/64 .005 .015 .005 ± .1°</p> <p>TOLERANCE SW PER ANSI Y14.5 REMOVE ALL DIMENSIONS FROM EXTERNAL DIMENSIONS .005 TO .015 FILES & DIMS TO .015 SCREEN THREADS PER UNF-5-8B79 DIMS ON A COLUMN & OF .005 MACHINED SURFACES V</p> <p>DO NOT SCALE DRAWING</p>		<p>DESIGNED BY: S. HUYNH</p> <p>DATE: Mar-19-09</p> <p>SCALE: 1/1</p>																																																																																											