



## Single Enclosure GPS/INS Receiver Delivers 3D Position, Velocity and Attitude Solution

### Benefits

Continuous, stable positioning

Easy to integrate into space constrained applications

Minimizes import/export issues

Withstands harsh environments

Proven OEMV® technology

### Features

Fiber optic gyros and MEMS accelerometers

SBAS, L-band and RTK support

100 Hz raw data and solution

Wheel sensor input for ground applications

### SPAN: World leading GPS+INS Technology

NovAtel's SPAN (Synchronous Position, Attitude and Navigation) technology brings together two different, but complementary technologies: GPS positioning and inertial navigation. The absolute accuracy of GPS positioning and the stability of inertial measurement unit (IMU) gyro and accelerometer measurements are tightly coupled to provide an exceptional 3D navigation solution that is stable and continuously available, even through periods when satellite signals are blocked.

### SPAN-CPT Overview

SPAN-CPT is a compact, single enclosure GPS+INS system, powered by NovAtel's world class, professional-grade OEMV technology. Capable of delivering up to one centimetre level accuracy, customers can choose from a variety of positioning modes to ensure they have the optimal level of accuracy for their application. Available modes including SBAS, L-band (OmniSTAR and CDGPS) and RTK.

The IMU components, integrated within the SPAN-CPT enclosure, are comprised of fiber optic gyros (FOG) and micro electrical mechanical systems (MEMS) accelerometers, and provide the best price/performance available. FOGs offer exceptionally long life and stable performance compared with other similar gyro technologies.

### SPAN-CPT Advantages

The tight coupling of the GPS and IMU measurements delivers the most satellite observations and the most accurate, continuous solution possible. Further, SPAN-CPT is comprised entirely of commercial components, which means cross-border difficulties involved with traditional GPS/INS systems are greatly minimized.

For improved accuracy, SPAN data can be post-processed using NovAtel's Inertial Explorer® software (IE).

To learn more about SPAN technology go to [www.improveyourgps.com](http://www.improveyourgps.com)

If you require more information about our SPAN products, visit [improveyourgps.com](http://improveyourgps.com)



[novatel.com](http://novatel.com)

[sales@novatel.com](mailto:sales@novatel.com)

1-800-NOVATEL (U.S. and Canada)  
or 403-295-4900

Europe 44-1993-85-24-36

SE Asia and Australia 61-400-833-601

ppm GmbH  
Grube 39a  
82377 Penzberg  
Germany

Tel: +49 (0) 88 56 8 03 09 80  
Fax: +49 (0) 88 56 8 03 09 88

[info@ppmgmbh.com](mailto:info@ppmgmbh.com)  
[www.ppmgmbh.com](http://www.ppmgmbh.com)



**SPAN System Performance<sup>1</sup>**

<b>Horizontal Position Accuracy (RMS)<sup>2</sup></b>	
Single Point L1	1.5 m
Single Point L1/L2	1.2 m
SBAS	0.6 m
CDGPS	0.6 m
DGPS	0.4 m
OmniSTAR	
VBS	0.6 m
XP	0.15 m
HP	0.1 m
RT-20™	0.2 m
RT-2™	1 cm+1 ppm
<b>Data Rates</b>	
GPS Measurement	5 Hz
GPS Position	5 Hz
IMU Measurement	100 Hz
INS Solution	Up to 100 Hz
Time Accuracy <sup>3</sup>	20 ns RMS
<b>Maximum Velocity<sup>4</sup></b>	<b>515 m/s</b>

**IMU Performance**

Gyro Technology	FOG
Gyro Output Range	±375°/s
Gyro Bias	±20°/hr
Gyro Bias Stability	±1°/hr
Gyro Scale Factor	1500 ppm
Angular Random Walk	0.0667°/√hr (max)
Accelerometer Range	±10 g
Accelerometer Bias	±50 mg
Accelerometer Bias Stability	±0.75 mg
Accelerometer Scale Factor	4000 ppm

**Physical and Electrical**

<b>Dimensions</b>	<b>152 x 168 x 89 mm</b>
<b>Weight</b>	<b>2.36 kg</b>
<b>Power</b>	
Power Consumption	15 W Max
Input Voltage	+9 to +18 VDC

**Antenna Port Power Output**

Output Voltage	+5 VDC
Maximum Current	100 mA

**Input/Output Connectors**

Power and I/O	MIL-DTL-38999 Series 3
Antenna Input	TNC Female

**Communication Ports**

RS232 UART COM	2
USB Device	1
CAN	1
Event Input Trigger	1
Configurable PPS	1

**Environmental**

Temperature	
Operating	-40°C to +65°C
Storage	-50°C to +80°C
Humidity	95% non-condensing
Waterproof	MIL-STD-810F, 506.4, Procedure I

**Included Accessories**

- Combined I/O and Power Cable

**Optional Accessories**

- GPS-700 series antennas (dual frequency required)
- Antcom antennas (dual frequency required)
- RF cables – 5, 10 and 30 m lengths
- Inertial Explorer post-processing software

For additional GNSS Specifications, please see:  
[novatel.com/Documents/Papers/OEMV3.pdf](http://novatel.com/Documents/Papers/OEMV3.pdf)

**Performance During GNSS Outages<sup>1,5</sup>**

Outage Duration	Positioning Mode	Position Accuracy (m) RMS		Velocity Accuracy (m/s) RMS		Attitude Accuracy (degrees) RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0s	RTK	0.03	0.02	0.020	0.010	0.015	0.015	0.050
	HP	0.10	0.08	0.020	0.010	0.015	0.015	0.050
	SP	1.20	0.60	0.020	0.010	0.015	0.015	0.060
	PP <sup>6</sup>	0.01	0.02	0.020	0.010	0.015	0.015	0.030
10 s	RTK	0.23	0.01	0.050	0.016	0.020	0.017	0.060
	HP	0.77	0.75	0.051	0.023	0.020	0.017	0.060
	SP	1.38	0.68	0.034	0.014	0.020	0.017	0.065
	PP <sup>6</sup>	0.03	0.03	0.020	0.010	0.016	0.015	0.032
60 s	RTK	5.71	1.60	0.212	0.059	0.028	0.028	0.090
	HP	6.47	1.69	0.240	0.071	0.028	0.028	0.095
	SP	7.12	1.89	0.260	0.075	0.028	0.028	0.100
	PP <sup>6</sup>	0.31	0.06	0.030	0.020	0.021	0.021	0.042



Version 2 - Specifications subject to change without notice.

© 2009 NovAtel Inc. All rights reserved.

NovAtel, Inertial Explorer and OEMV are registered trademarks of NovAtel Inc. SPAN, RT-2 and RT-20 are trademarks of NovAtel Inc.

Printed in Canada. D12768

SPAN-CPT December 2009

For the most recent details of this product:

[novatel.com/Documents/Papers/SPAN-CPT.pdf](http://novatel.com/Documents/Papers/SPAN-CPT.pdf)

<sup>1</sup> Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference.

<sup>2</sup> GPS only.

<sup>3</sup> Time accuracy does not include biases due to RF or antenna delay.

<sup>4</sup> Export licensing restricts operation to a maximum of 515 metres/second.

<sup>5</sup> RMS, incremental error growth from steady-state accuracy. Computed with respect to full GPS, RTK trajectory.

<sup>6</sup> Post-processing accuracy using Inertial Explorer processing software.



ppm GmbH  
 Grube 39a  
 82377 Penzberg  
 Germany  
 Tel: +49 (0) 88 56 8 03 09 80  
 Fax: +49 (0) 88 56 8 03 09 88

info@ppmgmbh.com  
[www.ppmgmbh.com](http://www.ppmgmbh.com)

